

## CLAIMS

What is claimed is:

- 1 1. A method of providing a protected execution environment on a computer  
2 comprising:  
3 intercepting an input/output request for a file from an application;  
4 determining if the application is authorized to modify the protected execution  
5 environment;  
6 creating a redirected input/output request to an alternate environment when the  
7 application is not authorized to modify the protected execution environment and the file  
8 is within the protected execution environment; and  
9 submitting the redirected input/output request to a file system manager.
- 1 2. The method of claim 1 further comprising:  
2 allowing the redirected input/output request to continue when it is intercepted.
- 1 3. The method of claim 1 further comprising:  
2 creating the protected execution environment.
- 1 4. The method of claim 1 wherein the protected execution environment comprises a  
2 directory for each of the applications that is authorized to modify the protected execution  
3 environment.
- 1 5. The method of claim 1 further comprising:  
2 categorizing each application installed on the computer as authorized or not  
3 authorized to modify the protected execution environment.

1 6. The method of claim 1 wherein the alternate environment comprises a directory  
2 associated with an application that is not authorized to modify the protected execution  
3 environment.

1 7. The method of claim 1 wherein the redirected input/output request specifies a  
2 directory in the alternate environment that corresponds to a directory in the protected  
3 execution environment specified in the input/output request.

1 8. The method of claim 1, wherein a parent-child relationship is maintained between  
2 an application that invokes another application.

1 9. The method of claim 1, wherein determining if the application is authorized to  
2 modify the protected execution environment comprises:  
3 designating the application as not authorized to modify the protected execution  
4 environment if the application was invoked by another application that is not authorized  
5 to modify the protected execution environment.

1 10. The method of claim 1, further comprising:  
2 creating a null entry in a mirror directory structure for an executable for each  
3 application authorized to modify the protected execution environment,  
4 wherein determining if the application is authorized to modify the protected execution  
5 environment comprises:  
6 querying the existence of the executable for the application in the mirror  
7 directory structure.

8 11. The method of claim 10, further comprising:

1 maintaining an association between an executing application and a directory path  
2 for the executable for the executing application,  
3 wherein querying for the existence of the executable in the mirror data structure  
4 comprises:  
5 specifying the directory path for the executable associated with the  
6 executing application.

1 12. A method for operating a computer system with a protected execution  
2 environment comprising:  
3 executing a configuration utility to categorize a plurality of applications installed  
4 on the computer system as authorized or not authorized to modify the protected execution  
5 environment;  
6 defining the protected execution based on the authorized applications; and  
7 installing a protected execution agent in a file system to intercept input/output  
8 requests submitted by the applications, wherein the protected execution agent directs an  
9 input/output request to an alternate environment if the application that submitted the  
10 request is not authorized and the request is directed to the protected execution  
11 environment.

1 13. The method of claim 12 wherein the configuration utility defines the protected  
2 execution environment when categorizing the plurality of applications.

1 14. The method of claim 12 wherein the alternate environment is defined based on at  
2 least one application that is not authorized.

004344-P003-040700-93254560

1 15. The method of claim 12, wherein the alternate environment is defined by the  
2 configuration utility when categorizing the plurality of applications.

1 16. The method of claim 12, wherein the configuration utility further creates a null  
2 entry in a mirror directory structure for an executable for each authorized application and  
3 the protected execution agent further queries the existence of the executable for an  
4 executing application in the mirror directory structure to determine if the application is  
5 authorized.

1 17. The method of claim 16, wherein the protected execution agent further maintains  
2 an association between the executing application and a directory path for the executable  
3 for the executing application.

1 18. The method of claim 12, wherein the protected execution agent designates a  
2 second application as not authorized if it was invoked by a first application that is not  
3 authorized.

1 19. The method of claim 18, wherein the protected execution agent maintains a  
2 parent-child relationship between the first and second applications.

1 20. The method of claim 12, wherein the protected execution agent is installed in a  
2 hook chain in a file system manager to intercept the input/output requests before the  
3 requests are processed by any other agent installed in the hook chain.

004344.P003 93254560

1 21. The method of claim 12, wherein the configuration utility is executed prior to  
2 providing the computer system to a user and the protected execution agent is installed  
3 each time the computer system is booted.

1 22. The method of claim 12, further comprising:  
2 saving a copy of the protected execution environment; and  
3 recovering from a failure of the computer system by replacing the protected  
4 execution environment with the copy.

1 23. The method of claim 22, wherein the copy is saved on the computer system in a  
2 secure location.

1 24. The method of claim 22, wherein the copy is saved on a remote computer server  
2 and downloaded to the computer system.

1 25. A method of determining a category for an application on a computer comprising:  
2 categorizing the application as a first type;  
3 creating a directory in a second directory structure for the application when it is a  
4 first type, wherein the second directory structure mirrors a first directory structure that  
5 contains an executable for the application;  
6 creating a null entry for the executable for the application in the directory in the  
7 second directory structure when the application is the first type;  
8 querying the existence of the executable for the application in the second directory  
9 structure, wherein the application is determined to be the first type when the executable  
10 exists.

004344.P003-0400

1 26. A computer-readable medium having stored thereon computer-executable  
2 instructions for performing a method comprising:  
1 intercepting an input/output request for a file from an application;  
2 determining if the application is authorized to modify the protected execution  
3 environment;  
4 creating a redirected input/output request to an alternate environment when the  
5 application is not authorized to modify the protected execution environment and the file  
6 is within the protected execution environment; and  
7 submitting the redirected input/output request to a file system manager.

1 27. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 allowing the redirected input/output request to continue when it is intercepted.

1 28. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 categorizing each application installed on the computer as authorized or not  
4 authorized to modify the protected execution environment.

1 29. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 creating the protected execution environment from a directory for each of the  
4 applications that is authorized to modify the protected execution environment.

1 30. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:

3 creating the alternate environment from a directory associated with an application  
4 that is not authorized to modify the protected execution environment.

1 31. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 storing a directory path specified in the input/output request in the redirected  
4 input/output request to direct the request to a corresponding directory path in the alternate  
5 environment.

1 32. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 maintaining a parent-child data structure to track between relationships between  
4 applications that invoke other applications.

1 33. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 designating the application as not authorized to modify the protected execution  
4 environment if the application was invoked by another application that is not authorized  
5 to modify the protected execution environment.

1 34. The computer-readable medium of claim 26 having further computer-readable  
2 instructions comprising:  
3 creating a null entry in a mirror directory structure for an executable for each  
4 application authorized to modify the protected execution environment; and

1 querying the existence of the executable for the application in the mirror directory  
2 structure when determining if the application is authorized to modify the protected  
3 execution environment

1 35. The computer-readable medium of claim 34 having further computer-readable  
2 instructions comprising:  
3 maintaining an association between an executing application and a directory path  
4 for the executable for the executing application; and  
5 specifying the directory path for the executable associated with the executing  
6 application when querying for the existence of the executable in the mirror data structure.

1 36. A computer system comprising:  
2 a processing unit;  
3 a memory coupled to the processing unit through a system bus;  
4 a computer-readable medium coupled to the processing through the system bus;  
5 and  
6 a protected environment agent executing from the computer-readable medium,  
7 wherein the protected environment agent causes the processing unit to intercept  
8 input/output requests submitted by applications executing on the computer system and  
9 further causes the processing unit to redirect each input/output request to an alternate  
10 environment if the application that submitted the request is not authorized to modify a  
11 protected execution environment and the request is directed to the protected execution  
12 environment.

1 37. The computer system of claim 36 further comprising:



2 a configuration utility executing from the computer-readable medium, wherein the  
3 configuration utility causes the processing unit to categorize each application installed on  
4 the computer system as authorized or not authorized to modify the protected execution  
5 environment and further to cause the processing unit to define the protected execution  
6 environment to contain directories associated with the authorized applications.

004344-040700